



FASTENING SYSTEM

GYPFAST



Corrosion Resistance:

Climacoat Long Life Polymer

- Salt Spray Results (ASTM B117)
Driven: 1560 hours, 10% or less red rust
UnDriven: 3240 hours, 10% or less red rust

Selection Chart

Part No.	Fastener Description .140" dia. Knurled Shank 5/16" dia. Bugle Head	Master Carton Quantity	Master Carton Weight	Applications
GF100	1" (25mm)	4,800 nails/ctn (48 - 100 ct. coils) 5 fuel cells	19 lbs.	Metal to Metal Attachment
GF112	1-1/2" (38mm)	6,000 nails/ctn (40- 150 ct. coils) 6 fuel cells	37 lbs.	Single Layer of Exterior Sheathing, Wood Furring and Blocking
GF200	2" (51mm)	4,800 nails/ctn (32 - 150 ct. coils) 5 fuel cells	38 lbs.	Double Layer of Exterior Gypsum Sheathing, Wood Furring and Blocking
GF212	2-1/2" (64mm)	2,700 nails/ctn (18 - 150 ct. coils) 3 fuel cells	26 lbs.	Multi-Layers of Sheathing, Wood Blocking, and Dimensional Lumber
GYPFAST	GypFast Cordless Coil Nailer 12 lbs. (1) Tool; (1) Safety Goggles; (1) Operators Manual			

Performance Data

Fastener	Board Type	Orientation	Gauge	Stud Spacing	Stud/Fastener
GypFast	5/8" Dens-Glass® Gold	Vertical	18	24"/8"	70.9
GypFast	5/8" Exterior Gypsum	Vertical	18	24"/8"	63.5

Fastener	Pullout				Avg. lbs. Ultimate Tensile	Avg. lbs. Ultimate Shear
	Steel Gauge					
	20	18	16	14		
GypFast	.036	.048	.060	.075	2041	1385
S-12 self-drilling screws	194	327	437	930	750	1430

Values are in average, ultimate pounds.

Accessories

Part No.	Description	Carton (Qty)
2761910	Lath Disc Magnetic Nose Piece	1
LD114	Lath Disc - 1-1/4"	1000
LD100	Lath Disc - 1"	1000
405176	Battery	1
TFUEL	Fuel Cell	12
7505142	Battery Charger	1

Tools and Techniques

- Always read operators manual for instruction on proper use and safety.
- Adjust depth sensitive nosepiece to achieve proper seating of fastener to work surface.
- Consult sheathing manufacturer's guidelines for appropriate fastener and fastening pattern.
- Point of nail must penetrate 1/2" minimum beyond steel.