



## DCN890 20V MAX\*

- Powered by 20V XR 5.0Ah Li-ion battery for extended run time (480 shots per charge in steel and 580 in concrete)
- DEWALT proprietary pins (13mm - 57 mm) gives a complete solution
- 3-Speed control (13,000, 14,000 and 15,000 RPM) enables fastening of different materials, saves time
- Removal foot gives more stability and reduces slipping
- Battery indicator provides warning information for ease of use
- Single or rapid mode selector for faster work completion
- Narrow nose for easy access
- Quick release for nose piece for ease and speed
- Stall indicator for easy diagnostics
- Stall release, tool free for ease and speed

## COMPATIBLE PINS

	DESCRIPTION	QTY
CONCRETE	DCN890075 DEWALT CCN PIN 3/4" X .102" (Z)	1000
	DCN890100 DEWALT CCN PIN 1" X .102" (Z)	1000
	DCN890125 DEWALT CCN PIN 1-1/4" X .102" (Z)	1000
	DCN890150 DEWALT CCN PIN 1-1/2" X .102" (Z)	1000
	DCN890225 DEWALT CCN PIN 2-1/4" X .137" (T Z)	500
	DCN891075 DEWALT CCN PIN 3/4" X .145" (Z)	1000
STEEL	DCN8910500 DEWALT CCN PIN 1/2" X .120" (Z)	1000
SPECIALTY	DCN8941380 DEWALT CCN PIN 1-3/8" X .108" (Z)	1000
	DCN8910680 DEWALT CCN PIN .680" X 120" / .102 (S YZ)	1000
	DCN8917300 DEWALT CCN PIN .730" X .120" / .102" (S YZ)	1000
	DCN8907804 DEWALT CCN PIN .780" X .102" / .088" (K S Z)	1000

K: Knurled S: Step T: Tapered YZ: Yellow Zinc Z: Zinc



## COMPATIBLE ACCESSORIES

DCN8901 REPLACEMENT DRIVER BLADE	DCN8902 MAGNETIC STICK-E™ CONTACT TRIP	DCN8903 STICK-E™ CONTACT TRIP	DCN8904 STANDARD/DRYWALL CONTACT TRIP
DCN8905 POLE TOOL			

