

SIZES

MECHANICAL PIN WITH WASHER

Used for the attachment of light gage metal to concrete and steel such as HVAC duct strap to concrete

PLATED PIN PREASSEMBLED TO A 1/2" DOMED WASHER. 200 PER BOX.



PART NUMBER	DESCRIPTION	M150	E150/ T150	R150*	T3SS*
M012	1/2" Plated step pin with domed washer	■		■	■
M034	3/4" Plated pin with domed washer	■		■	■
M034BB	3/4" Premium step pin with domed washer	■		■	■
M100	1" Plated pin with domed washer	■		■	■

Shank diameter = .125, Step Pin .104/.118

Head diameter = .300 (M012 = .250)

* Will fit R150 & T3SS with optional work contact element, P/N: M150200

1/4-20 THREADED STUD

Used to attach electrical components to concrete where removability of the component is required

PLATED THREADED STUD. 200 PER JAR.



PART NUMBER	THREAD LENGTH	SHANK LENGTH	M150	E150/ T150	R150	T3SS
14STUD	1/2"	5/8"		■	■	■

Shank diameter = .125,

TOP HAT PIN

Used for general purpose fastening to concrete

PLATED PIN WITH TOP HAT. 200 PER JAR.



PART NUMBER	DESCRIPTION	M150	E150/ T150	R150	T3SS
MP034TH	3/4" Plated pin with top hat		■	■	■

Shank diameter = .125

Head diameter = .300

BRIDLE RING

Pre-Assembled 2" Bridle Ring supports low voltage, data com, signal, and control cables

50 PER BOX.



BR2



BR200



BR2S

PART NUMBER	DESCRIPTION	E150/ T150	R150	T3SS
BR2	2" bridle ring	■	■	■
BR200*	2" bridle ring w/o fastener, w/attached washer	■	■	■
BR2S	2" bridle ring saddle	■	■	■

Shank diameter = .125

* For use when fastening with, Powder Actuated Tools, Tapcon, or conventional drill and anchor methods.